







ZEDGE LINE REMOTE

ZEL - RP
ZLO - RP

ZEDGE LINE REMOTE
ZEDGE LINE OPAL REMOTE



*If in doubt about the symbols
refer to catalog or website*



WARNING

**To ensure a maximum efficient use
of the product, read the instructions
before proceeding installment.**



This fixture must be installed by a
licensed and qualified electrician. The
installer must comply with NEC and local
building codes when installing the fixture



Electrical current can cause painful
shock, serious injury, or even death.
Make sure you turn off the power supply,
ground fixture(s), and make sure all
electrical connections are correct and
secured tightly



For use in IP66 installations.




Keep the label of the original packaging if
any eventual future claims are needed

Table of Contents

Packaging Contents	Pg.2
Fixture Connection	Pg.3
Installation Type A and B	Pg.4
Installation Without Back Box	Pg.5
Maintenance / Support	Pg.6

Packaging Contents



BOX 14"x4"x3.5" @1.54 lbs.




HEAT-SHRINK WATERPROOF
CONECTOR



4" HEAT-SHRINK TUBE


LED FIXTURE ANY OPTION 1 ea.

3ft 18ga - 2 Conductor Cable



ZEL-RP
ZEDGE LINE

3ft 18ga - 2 Conductor Cable




ZLO-RP
ZEDGE LINE OPAL


FIXTURE CONNECTION

Zedge Line back box **1E3447**

*See Back box installation instructions for details.



Wiring Diagram




Max Fixtures Per Driver

Fix. Qty.	Load	18gauge	16gauge	14gauge	12gauge
1-3 fixtures	to 18w	72 ft.	115 ft.	180 ft.	290 ft.
4-6 fixtures	to 36w	42 ft.	67 ft.	106 ft.	165 ft.
7-8 fixtures	to 48w	28 ft.	44 ft.	70 ft.	112 ft.
9-10 fixtures	to 60w	20 ft.	33 ft.	52 ft.	84 ft.
11-13 fixtures	to 78w	16ft.	26 ft.	41 ft.	66 ft.

INSTALLATION TYPE 'A' AND "B"


INSTALLATION TYPE "A" FLUSH MOUNTING

1E3447 Used with flush ring attached




INSTALLATION TYPE "B" FLANGED MOUNTING

1E3447 Used with flush ring detached




INSTALLATION WITHOUT BACK BOX

Using 1T7003 Spring Clips






ZEDGE LINE



+

1T7003




24V DC

0.20 - 1.18in
MIN-MAX

11.6in

2.17in

*Connect with supplied waterproof connectors for single fixture connection runs. Not for Daisy Chained multi fixture runs.



Maintenance

This fixture was designed and manufactured for a durable, long lasting use with minimum care. To ensure the maximum lifespan of this product, we encourage our customer to provide a quality visual inspection of the fixture and installation accessories every six months. If there are any visible signs of issues (i.e moisture or dust) during the inspection, please clean any of the dust or moisture with a soft cloth and check to make sure that any of the fixtures are still operating normally. If there are any issues regarding the fixture please contact us as we will assist the situation at hand.

Support

Any questions, problems, or comments you have please feel free to contact our Customer Service department during our business hours Monday-Friday 8am-5pm via: Email: usaorders@targetti.com
Phone: (714) 513-1991

Visit our website: <http://www.targettiusa.com>